## HOME RETROFIT SPECIFICATIONS MANUAL

## GAS FURNACE COMPLETE MEASURE CHECKLIST

All work must meet Energy Trust of Oregon specifications. **This checklist serves as a reference guide only**. Please refer to the current Specifications Manual for additional information and clarification. Specific reference sections are noted in italics.

|             | A functioning UL-listed carbon monoxide alarm is installed in the home on every floor with a bedroom and according to manufacturer's specifications. <i>IN 1.2</i>  |            |       |
|-------------|---|------------|-------|
|             | Unit has a permanent label identifying make, model and serial number. IN 1.14   |            |       |
|             | Unit is installed in a non-hazardous location maintaining proper clearance and does not compromise the structural integrity of the building. <i>IN 1.14 and IN 1.15</i>   |            |       |
|             | Entire gas line from meter to appliance is free of leaks. IN 1.15   |            |       |
|             | Intake air comes from outside the conditioned space. <i>GF 1.2</i>  |            |       |
|             | If applicable, any orphaned water heater complies with WH 2.1—exhaust flue ducting is properly sized and maintains adequate slope, unit shows no signs of combustion gas spillage or flame rollout. <i>GF 1.1</i> |            |       |
|             | Unit is installed in accordance with manufacturer's specifications and jurisdictional codes. IN 1.14  |            |       |
|             |   |            |       |
| Print Name: |   | Signature: | Date: |